

# (12) United States Patent

#### Kaminaka et al.

## (54) STAINLESS STEEL SHEET FOR A SEPARATOR FOR A SOLID POLYMER FUEL CELL AND A SOLID POLYMER FUEL CELL EMPLOYING THE SEPARATOR

(75) Inventors: Hideya Kaminaka, Nishinomiya (JP);

Junko Imamura, Amagasaki (JP); Akira Seki, Ashiya (JP); Kouichi

Takeuchi, Chofu (JP)

(73) Assignee: NIPPON STEEL & SUMITOMO METAL CORPORATION, Tokyo (JP)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 713 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 13/080,937

(22)Filed: Apr. 6, 2011

**Prior Publication Data** (65)

US 2011/0250522 A1 Oct. 13, 2011

## Related U.S. Application Data

(63) Continuation of application No. PCT/JP2009/ 067512, filed on Oct. 7, 2009.

#### (30)Foreign Application Priority Data

Oct. 7, 2008	(JP)	2008-260873
Nov. 14, 2008	(JP)	2008-292367
Oct. 7, 2009	(JP)	2009-233511

(51) **Int. Cl.** H01M 8/021 C22C 38/40

(2016.01)(2006.01)

(Continued)

(52) U.S. Cl. CPC ...... H01M 8/021 (2013.01); C22C 38/40 (2013.01); C22C 38/44 (2013.01);

(Continued)

## (10) Patent No.:

US 9,680,162 B2

(45) Date of Patent:

\*Jun. 13, 2017

#### (58) Field of Classification Search

None

See application file for complete search history.

#### (56)References Cited

### U.S. PATENT DOCUMENTS

5,789,086 A \* 8/1998 Ohmi ...... C23C 8/14 6,420,070 B1\* 7/2002 Kasamatsu et al. ...... 429/231.8 (Continued)

#### FOREIGN PATENT DOCUMENTS

1271027 10/2005 CN EP 1 094 535 4/2001 (Continued)

#### OTHER PUBLICATIONS

"Interlayer interactions in graphite and carbon nanotubes" by Palser et al, Phys. Chem. Chem. Phys. (1999) 1:4459-4464.\* (Continued)

Primary Examiner - Patrick Ryan Assistant Examiner — Carmen Lyles-Irving (74) Attorney, Agent, or Firm — Clark & Brody

#### (57)ABSTRACT

A stainless steel member for a separator of a solid polymer fuel cell has excellent cell properties with little deterioration in performance over long periods of operation without worsening of the corrosion resistance of a stainless steel separator. The stainless steel member has a stainless steel base metal, and a passive film and electrically conductive precipitates both provided on a surface of the stainless steel base metal. The electrically conductive precipitate penetrates the passive film and includes a substance originating from the stainless steel base metal. An electrically conductive layer comprising a nonmetallic electrically conductive substance is preferably provided on the surface of the passive film, and the electrically conductive layer is prefer-(Continued)



